How to set up the BraunAbility Remote app

- I. Download the BraunAbility Remote app from Google Play or App Store.
- 2. Activate Bluetooth on your smartphone.
- 3. Run the Turny Evo to a position where the Teach-in button (A) on the receiver is accessible. You have to lift the curtain to access the button.
- 4. Press the teach-in button ×3 and follow the setup wizard in the app.

Turny Evo from above, swiveled out to the right.



Before using this device, download and read the user manual available at: www.braunability.eu

BraunAbility Europe AB

Åkerivägen 7 443 61 Stenkullen Sweden Phone: +46 302 254 00 E-mail: info@braunability.eu www.braunability.eu

BraunAbility[•]



BRAUNABILITY REMOTE

Quick guide for Turny Evo



Install the receiver to a Turny with six wires

- Swivel and extend the Turny Evo as far out as possible.
- Unscrew the curtain and feed it back in its roll. This will keep it from getting caught during the rest of the installation.
- Attach the supplied cable to the Turny Evo (A) by connec-3. ting the coloured cables to their matching counterpart using the splices.
- Connect the receiver to the supplied cable (B). Attach the 4. receiver at the position (C) using the double sided adhesive pads.
- Carefully loop the cables and attach them underneath the 5. swivel motor using the cable tie. Ensure that no cables are pinched when the unit is in motion.
- Run the Turny Evo to a position where the protective 6. cover of the control board (D) is fully visible.
- Remove the protective cover for the control board.
- 8. Locate the cable (E) for the Turny Evo remote interface next to the swivel motor and attach the connector (F) to the control board. Reattach the protective cover.
- Pull out the curtain and reattach with the screw.

Install the receiver to a Turny with one socket

- Swivel and extend the Turny Evo as far out as possible.
- Unscrew the curtain retaining screw and feed curtain back in its roll. This will keep it from getting caught during the rest of the installation.
- 3. Connect the receiver to the socket (B) on the Turny Evo. Align the receiver with the holes at the position (C). Fasten using the supplied screws and spring washers.

- 4. Carefully route the cables and secure them underneath the swivel motor using the cable tie. Ensure that no cables are pinched when the unit is in motion.
- 5. Pull out the curtain and reattach with the screw.

Seat Place flush along this edge 5 cm Swivel motor Adhesive pads x4 ∃B≒ 0 Receiver (A) Align with the holes (applies to Turny Evo with one socket)

Turny Evo from above, swiveled out to the right.